

## AW-GEC2159 Automatic Gas Extinguisher Control Panel

### Profile

The AW-GEC2159 automatic gas extinguisher control panel is a combined fire alarm control panel and extinguishing system and has 4 detection zones, any or all of which are capable of contributing to the extinguishant release.

### Technical Parameters

- Mains Supply: 90 to 270VAC, 50Hz/60Hz
- Mains Supply Fuse: 3 Amp ( F3A L250V)
- Battery Charge Voltage: 27.6VDC nominal
- Detection circuit: 4 zones

### Packing Details

Size: 340mm×275mm×100mm  
Weight: 5kg



**AW-GEC2159**



**AW-MS2159**



**AW-MRS2159**



**AW-GRS2159**

Product Name	Maintenance Switch	Manual Release Station	Gas Release Warning Signage
Model No.	AW-MS2159	AW-MRS2159	AW-GRS2159
Operating Voltage	DC24V	DC24V	DC24V/AC24V Non-polarized
Other Specific Details	Switch Rated: 5A 250VAC DC Rating : 5A up to 30VDC LED Rated: 10mA each for a total current draw of 20mA.	The Manual Release Station is connected with Fire Fighting Panel.	Working Current: ≤70mA @ 24 VDC Flash Period: 1.2-1.5 Sec

WE SUPPLY FREE DESIGN SERVICE FOR CUSTOMERS  
WE SUPPLY THE RE-FILLING MACHINE FOR FM200 CYLINDERS.

FM200 (HFC-227ea) is the clean agent for fire extinguishing System.

FM200 is a colorless, non-toxic gas perfectly suited to protect high value assets in areas that may be normally occupied, in locations where clean-up of other agents is problematic, when storage space for a fire suppression agent is restricted, or when an electrically non-conductive agent is required.

ASENWARE Gas Fire Extinguishing Control System has 2 types: Cabinet type and Manifold type.

### Cabinet Type



**40L      70L      90L      120L      150L**

### Parameters:

Model No.	Cylinder Capacity	Cabinet Size L*W*H(mm)	Gas Storage Pressure
AW-FMCB4025	40 L	560*530*1670	2.5MPa
AW-FMCB7025	70 L	590*530*1670	2.5MPa
AW-FMCB9025	90 L	640*540*1870	2.5MPa
AW-FMCB12025	120L	690*590*1790	2.5MPa
AW-FMCB15025	150L	690*590*1720	2.5MPa